

LF-GIF050YK1300U(S)

SELV Flicker Free LED Driver | Constant Current - Non Dimmable



Product family features

- Low THD $\leq$ 20% @full load
- Rated input range: 120–277Vac
- Ta range: -30 - +45 °C
- Ripple current $\leq$ 5%
- 5 years guarantee
- Lifetime up to 100,000h



Product family benefits

- Compact size, independent use, and high PF
- Flicker free
- Current adjustable via DIP switch
- SELV output

Typical applications

- For panel light, down light
- For office, commercial, and decorative lighting

Product parameters

- Output current 1100/1200/1300mA
- Output power 26.4-49.4W
- Input voltage 108–305Vac
- Output voltage 24-40Vdc
- Efficiency 91.5%

Electrical data

Input data

Rated AC input voltage	120 ... 277V
AC voltage range	108 ... 305V
Mains frequency	50/60Hz
Rated DC input voltage	/
DC voltage range	/
Power factor	0.97 ¹⁾ @230Vac
Efficiency	91.5% @230Vac; 90% @120Vac
THD	≤20%
Input current	0.65A Max
Inrush current	90A ²⁾
Loading number on circuit breaker 10 A (B)	5
Loading number on circuit breaker 10 A (C)	9
Loading number on circuit breaker 16 A (B)	8
Loading number on circuit breaker 16 A (C)	14
Protective conductor current	≤0.7mA

Output data

Nominal output voltage	24...40V ³⁾
Nominal output current	1100/1200/ 1300mA
Default output current	1100mA
Current setting	DIP Switch (see the DIP switch definition for the corresponding current)
Maximum output power	49.4W
Nominal output power	26.4 ... 49.4W
Output ripple current (100 Hz)	<5%
Flicker	According to IEEE Std 1789-2015
CIE SVM	≤0.4
IEC-Pst	≤1
Current tolerance	±5%
Temperature tolerance	±10%
Start-up time	<0.5S

Safety

Withstanding voltage	I/P-PG: 3.75kV&5mA&60S
Surge capability (L-N)	1kV
Surge capability (L/N-Ground)	-
Insulation resistance	I/P-PG: >100MΩ@500Vdc
Lifetime	Up to 100,000 hours ⁴⁾
Guarantee	5 years ⁵⁾

1) @1200mA/1300mA full load

2) t =120μs


3) Please refer to the operating window about the relation between output voltage and output current

4) For details, please refer to the service life table


5) 5 years@Tc≤80°C

Characteristic diagrams


Operating Window




Typical Efficiency vs Load




Typical Power Factor vs Load



Typical THD vs Load



Lifespan




Service life

Model	I _{out}	P _{out}	T _a	35°C	45°C
LF-GIF050YK1300U(S)	1300mA	49.4W	T _c	70°C	80°C
			Lifetime	>100,000h	>50,000h

Note: The design life of the LED driver is as described above under reference conditions. The failure probability is less than 10%.

The relationship between T_c and T_a also depends on the design of the luminaire.

Dimensions (Unit: mm)



Mounting hole spacing, length	102.7±0.2mm
Positioning hole diameter	4.3mm
Product weight	100g
Cable cross-section, input side	0.75 ... 1.5 mm²
Cable cross-section, output side	0.2 ... 1.5 mm²
Cable outside diameter, input side	Max: 5.0mm Min: 3.0mm
Cable outside diameter, output side	Max: 5.0mm Min: 3.0mm
Wire preparation length, input side	7...8mm
Wire preparation length, output side	7...8mm
Length	115.0±0.2mm
Width	41.0±0.2mm
Height	28.0±0.2mm

Colors & materials


Casing material	PC
Casing color	White

Temperature & operating conditions

Ambient temperature range	-30 ... +45°C
Maximum temperature at t _c test point	80°C
Temperature range at storage	-30 ... +80°C (6 months in Class I environment)
Humidity range at storage	10-95%RH (no condensation)

Humidity during operation	20-90%RH
RoHS	RoHS 2.0 (EU) 2015/863

Tc test point (Unit: mm)



Tc point is on the top of the product

Product terminal

Input		Output	
AC-L	AC live wire input	LED+	Positive terminal output of LED driver
AC-N	AC neutral wire input	LED-	Negative terminal output of LED driver

DIP switch definition

Vo DC	I rated (CC)	1	2
24-40V	1100mA	-	-
24-40V	1200mA	ON	-
24-40V	1200mA	-	ON
24-38V	1300mA	ON	ON

Note: "-": shift OFF. "*": default current. DIP when power on is NOT allowed. Please disconnect the AC power before DIP.

Capabilities

Dimmable	-
Over-temperature protection	When the chip temperature hits over-temperature regulation point, output current will gradually decrease
Overload protection	-
Short circuit protection	Automatic reversible
No-load protection	<55V
Suitable for fixtures with prot. class	II
Control interface	-
Output interface	1 channel

Programming

Programming device	-
--------------------	---

DALI control software	-
APP	-
Certificates & standards	
Approval marks – approval	ENEC, CB, CE, RCM, SAA
Standards	EN/IEC 61347-2-13; EN/IEC 61347-1; EN/IEC 62384; EN 62493; AS 61347.2.13 & AS/NZS 61347.1
EMC	EN IEC 55015, EN IEC 61547, EN IEC 61000-3-2, EN 61000-3-3
Type of protection	IP20

Logistical data

Product	Packaging unit (Pieces/Unit)	Dimensions (L*W*H)	Volume	Gross weight
LF-GIF050YK1300U (S)	108	385mm*285mm*210mm	23.04 dm ³	17kg±5%

Test equipment & condition

Test equipment	AC power source: CHROMA6530, digital power meter: CHROMA66205, oscilloscope: Tektronix DPO3014, DC electronic load: M9712B, LED board, constant temperature and humidity chamber, lightning surge generator: Everfine EMS61000-5B, rapid group pulse generator: Everfine EMS61000-4A, spectroanalyzer: KH3935, hi-pot tester: EEC SE7440, flicker tester (flicker-free coefficient test): Everfine LFA-3000, etc.
----------------	---

If there are no special remarks, the above parameters are tested at the ambient temperature of 25℃, humidity of 50%, maximum output power and input voltage of 230Vac/50Hz.

Additional information

1. It is recommended that user install the over voltage protection, under voltage protection and surge protection devices in the power supply circuits of light fixtures to ensure electricity safety.

2. The LED driver used in combination with the end device is one of the accessories of the whole light fixture, and the EMC of the whole light fixture is not only susceptible to the driver itself, but to the LED light fixture and the whole light fixture's wiring. Thus, the manufacturer of LED light fixture should re-confirm the EMC of the whole light fixture before the whole light fixture is finished.

3. The number of LED drivers that can be connected to a circuit breaker and the inrush current are tested under the same conditions.

4. The PC cover, casing and end cap for assembling the LED driver in the light fixture must meet the fire rating of UL94-V0 or above.

Transportation & storage

Suitable transportation means: vehicles, boats and aeroplanes.

In transit, it is necessary to prepare awnings for rain or sun protection. Moreover, please keep civilized loading and unloading to prevent the vibration or impact on LED driver as much as possible.

The storage of LED driver shall conform to the standard of Class I environment.

1. When using the products which have been stored for more than 6 months, please re-test their electrical parameters firstly by powering on. Do not use them unless they are tested to be qualified.

2. When using the products which have been stored for 6 to 12 months, please run them on power for more than 2 hours firstly.

3. When using the products which have been stored for more than 12 months, please conduct an actual assessment of quality risks firstly. Direct use is not recommended.

Cautions

Please use Lifud LED driver according to its parameters in the specification, otherwise the LED driver may malfunction.

Using any incompatible light fixtures or those that have not been certified may cause fire, explosion or other risks.

Man-made damage is beyond the scope of Lifud warranty service.

Disclaimer

Subject to change without notice. Errors and omissions excepted. Always make sure to use the most recent release.

Lifud Technology Co., Ltd. reserves the right to interpret any content of this specification.